



# H.B. Fuller

## ETERNABOND®

### EternaPrime®

#### Description

**EternaPrime®** is a specially formulated primer developed specifically for **EternaBond®** tapes. **EternaPrime®**, based on a VOC exempt solvent, meets all federal standards for health and environmental safety.

**EternaPrime®** is designed to work with all **EternaBond®** tapes and was specifically developed for preparation of surfaces when installing **EternaBond®** tapes in low ambient temperatures from 4.4°C down to -28.9°C. It is also widely used as a coalescing agent on surfaces which have difficult to remove dirt or conditions which may encapsulate the **EternaBond®** tape.

\*Do not use on PVC.

#### Basic Use

**EternaPrime®** is used to prepare surfaces for application of all **EternaBond®** tapes. Recommended uses include, but are not limited to dirty surfaces which are difficult to clean completely (tar and gravel), potentially loose surfaces (mortar), porous surfaces (wood or concrete), and anytime the **EternaBond®** tape is applied at temperatures below 4.4°C ambient.

#### Composition

**EternaPrime®** is based on a VOC exempt solvent with a blend of our elastomers and resins infused into the solvent.



#### Technical Data

Application temperature	-28.9°C to 96.1°C
Coverage	300+ Sq. Ft. per gallon
Drying time at 15.6°C	15 minutes
Film thickness	+/- 4 mils when wet
Flash Point	43°C
Standard can sizes	14 oz spray 1 quart 1 gallon
Standard case quantity	12 14 oz spray per case 12 quarts per case 1 gallon per case
Viscosity	135 - 152 cps
Weight	6 lbs. per gallon

Values are typical performance properties and characteristics based on laboratory testing. This is intended as a guide for comparison purposes and does not constitute a specification or specification range.

CAUTION: All statements and technical information in this document are based on tests or data that H.B. Fuller believes is reliable. However, H.B. Fuller does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of H.B. Fuller's products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of H.B. Fuller's product with the design, structure, and materials of the user's end product and the suitability of H.B. Fuller's product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.

## Surface Preparation

Surface must be clean and dry. Remove heavy accumulations of loose rust and scale, dust, talc, and dirt. Oil and grease, and other contaminants should be removed with **EternaClean™** or a non-residue cleaner. Do not use **EternaPrime®** on PVC roofs as reactivation of some plasticizers may occur.

## Application

**EternaPrime®** can be rolled, or brushed onto surface (stir frequently).

## Shelf Life

Twenty-four months for unopened one gallon can.



Code 0207-1119

WARRANTY: H.B. Fuller warrants its products to conform to H.B. Fuller's specifications at the time of sale when tested according to H.B. Fuller standards. If a product is proven to be defective when tested according to H.B. Fuller standards, H.B. Fuller will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST H.B. FULLER AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall H.B. Fuller be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.