



- The Thermobit kettle for melting bitumen has been designed and made by Calloni taking into consideration every single detail to make its use easier and to get the maximum level of safety on job site. This kettle allows the preparation of the bitumen in just 20/25 minutes, thanks to the power of its three or five nozzles. It is composed of two separable parts which assure a complete distribution of the heat all over the kettle and keep it inside thanks to an insulating hollow space. Moreover, in order to get a higher safety level on site, the Thermobit kettle can be supplied with an overspill tray for possible undesirable overspill of melted bitumen during operation. It would be better to clean the kettle frequently for a constant output and a minimum consumption. The Thermobit kettle is available in two different sizes.



■ **Thermobit kettle for melting bitumen complete kit (Available sizes 150 Lt and 250 Lt)**

It includes:

- Thermobit kettle
- Burner
- Rubber hose EN ISO 3821
- Regulator with safety valve
- 1" ½ tap

A - Thermobit kettle Complete Kit

SPECIFICATIONS					
Code	Capacity	Weight	Length	Width	Height
	lt	Kg	cm	cm	cm
1007.150	lt. 150	106	145	60	95
1007.250	lt. 250	137	165	75	95



B - Outer case

SPECIFICATIONS					
Code	Capacity	Weight	Length	Width	Height
	lt	Kg	cm	cm	cm
1007.E150	lt. 150	63	135	60	84
1007.E250	lt. 250	77	155	75	84



C - Inner pan with tap

SPECIFICATIONS					
Code	Capacity	Weight	Length	Width	Height
	lt	Kg	cm	cm	cm
1007.I150	lt. 150	40	125	60	51
1007.I250	lt. 250	56	144	75	51