

Via Alu

aluminum solvent base
bituminous paint



Description: Solvent-based decorating protective paint containing aluminium.

Fields of application: It is used as a protective paint for polymer-bitumen membranes, giving them a brilliant silver color appearance. It is also suitable for decorating cold bituminous blankets.

Application: the product is frostproof. Do not expose the packagings at a temperature above 40°C. The paint appears soft and well suspended, with low sediment. It just needs to be slightly mixed to obtain a homogeneous and easier to apply product. It is ready to use and can be applied by spray (using Airless Spray), roller or brush. Before application, the bituminous surfaces to be treated must be perfectly clean. We suggest to apply it in dry and good weather on surfaces with falls for the regular flow of rainwater. It is unadvisable to apply it in summer season, on very hot surfaces during the hottest hours of the day. The yield per coat is approximately 150-200 g/m². Two coats are recommended where longer lasting, higher protection is required. To maintain a proper membrane painting we recommend to paint every 5 years approximately. Clean tools with common synthetic or nitrous thinners.

FEATURES	MEASURE UNIT	VALUES
Aspect		Silver liquid
Specific weight	Kg/L	0,95-1,15
Solids in weight (130°C)	%	50-58
Din Viscosity (+20°C)	seconds	20-35
Deep drying time	hours	4
Drying time to touch	minutes	100-140
Dust free drying time	minutes	30-60
Closed Flash point	°C	21
Shelf life in closed original pots	months	24

QUANTITY	5L	10L	20L
n. x Pallet	150	80	33
Lt x Pallet	750	800	660



Vetroasfalto SpA
Via Pascoli, 3 - 20060 Basiano (MI) - Italy
tel +39.02.959831 - fax +39.02.95983555
email: export@vetroasfalto.com
www.vetroasfalto.com
Quality Assurance : UNI EN ISO 9001:2008
Certificate : 0546/CPD-16876

