

Bitumen Paint

easy-trim WeatherProofing

Section 1: Identification of the mixture and of the company undertaking

1.1 Product Identifier

Product Name Bitumen Paint

1.2 Relevant identified uses of the mixture

Identified Use PC9a: Coatings and paints, thinners, paint removers.

1.3 Details of the suppliers of the safety data sheet

Supplier

EASY-TRIM ROOFING & CONSTRUCTION PRODUCTS LIMITED
UNIT 12B METCALF DRIVE
ALTHAM INDUSTRIAL ESTATE
ALTHAM
BB5 5TU

+44 (0) 845 034 6008 (Mon-Fri 08.30 - 17.30hrs. opening hours)
+44 (0) 845 034 6010 (Fax)

1.4 Emergency contact details

Outside of office hours (as listed above),
contact: +44 (0) 845 034 6008 Email: technical@easy-trim.co.uk

Section 2: Hazards identification

2.1 Classification of the substance mixture EC1272/2008

Classification under CHIP:

-: R10; N: R51/53; Xn: R65; -: R66; -: R67

Classification under CLP:

STOT SE 3: H336;
Aquatic Chronic 2:
H411; Asp. Tox. 1:
H304; Flam. Liq. 3:
H226; -: EUH066

Most important adverse effects:

Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

2.2 Label elements

Label elements under CLP:

Hazard statements:

EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Signal words:

Danger


Hazard pictograms:

GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



Precautionary statements:

PP280: Wear protective gloves/protective clothing/eye protection/face protection.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261: Avoid breathing vapours.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331: Do NOT induce vomiting.

P370+378: In case of fire: Use powder or foam for extinction.

Label elements under CHIP:

Hazard symbols:

Dangerous for the environment.

Harmful.



Risk phrases:

R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

Bitumen Paint

Section 2: Hazards identification - Cont.

Risk phrases - Cont:

R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases:

S2: Keep out of the reach of children.
S29: Do not empty into drains.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

Other hazards:

Harmful: may cause lung damage if swallowed.

PBT:

This product is not identified as a PBT/vPvB substance.

Section 3: Composition of ingredients

3.2. Mixtures

Hazardous ingredients:

WHITE SPIRITS

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-: R10; N: R51/53; -: R66; Xn: R65;	Flam. Liq. 3: H226; STOT SE 3: H335;	30-50%
		-: R67	STOT SE 3: H336; Asp. Tox. 1: H304;	
			Aquatic Chronic 2: H411; -: EUH066	

Section 4: First aid measurements

4.1 Description of first aid measures

Skin Contact

Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact

Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion

Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation

Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin Contact

There may be irritation and redness at the site of contact.

Eye contact

There may be irritation and redness. The eyes may water profusely.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

Section 4: First aid measurements - Cont.

Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
---------------------	---

5.2 Special hazards arising from the mixture

Exposure Hazardous	In combustion emits toxic fumes.
--------------------	----------------------------------

5.3. Advice for fire-fighters

Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
---------------------------	--

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.
-----------------------	--

6.2. Environmental precautions

Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
----------------------------	---

6.3. Methods and material for containment and cleaning up

Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
----------------------	--

6.4. Reference to other sections

Reference to other sections:	Refer to section 8 of SDS.
------------------------------	----------------------------

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements:

Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:

Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Storage conditions:

No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

No data available.

DNEL/PNEC Values

No data available.

8.2. Exposure controls

Engineering measures:

Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Hand protection:

Impermeable gloves.

Eye protection:

Safety glasses. Ensure eye bath is to hand.

Skin protection:

Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:

Liquid

Colour:

Black

Odour:

Aromatic

Solubility in water:

Insoluble

Viscosity:

Highly viscous

Boiling point/range°C:

>35

Flash point°C:

38°C

9.2. Other information

Other information:

No data available.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

Section 10: Stability and reactivity

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Avoid strong oxidising substances. Strong acids.

10.6 Hazardous decomposition products

In combustion emits toxic fumes.

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1 Toxicity No data available.

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:

Transfer to a suitable container and arrange for collection by specialised disposal company.

NB:

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PPAINT RELATED MATERIAL (OXIDIZED ASPHALT; STRAIGHT RUN KEROSENE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. mixture)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information:

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Paint

Section 16: Other information - Cont.

Phrases used in s.2 and s.3: Cont.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations:

PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration IC50 = median inhibitory concentration dw = dry weight bw = body weight cc = closed cup oc = open cup MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Disclaimer

The information relates only to this specified material and may not be valid for such materials used in combinations with other materials and processes. This information is, to the best of the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of the information on the material for their own particular use.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

