

# TECHNICAL DATA SHEET

## PRODUCT



**Ventilated Copper Ridge Roll**  
4 x 390mm rolls per box



**High Quality Butyl adhesive tape adheres to any roofing finish once clean and dry**



## USES

- Dry fix ventilation ridge and hip roll systems for slate, concrete or clay roof coverings
- Universal solution to suit round and angled ridge tiles
- Suitable for new and retro-fit projects on roof pitches from 15-55°

## FEATURES & BENEFITS

- Provides 5000mm<sup>2</sup>/m ventilation between ridge tiles on any flat or pan tile and slates
- Protects roof ridge tiles against water ingress, snow, insects and general deterioration over time
- Vapour permeable geotextile roll with two strips of pleated copper.
- UV stable providing long product life
- Various widths available to pre order
- Quick and easy to install, in most weather conditions with no special tools required
- Mechanically secure roof ridge tiles to help meet BS5534 & ICP2 code of practice for slating and tiling.
- Strong, malleable and corrosion resistant copper flashing.

## Product Details

<b>Ventilation Area</b>	5000mm <sup>2</sup> /m
<b>Size</b>	Roll size 5m x 390mm
<b>Non stock size to special order</b>	5m x 230mm 5m x 300mm 5m x 310mm
<b>Material</b>	Geotextile roll with pleated copper edge.
<b>Colour</b>	Copper
<b>Code</b>	Copper - DR51CP